

# Fuga-Soap Eco

**Eco-friendly detergent to remove residues and streaks of Fugalite® Eco, ideal for use GreenBuilding. Water-based concentrate, safeguards the health of both operators and the environment.**

Fuga-Soap Eco is an effective and specific detergent for use in cleaning after laying as it can be used in the routine maintenance of ceramic tiles, porcelain tiles and natural stone.



**GREENBUILDING RATING®**

		Water-based formulation		No environmental hazard rating	Non-toxic and non-hazardous

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

**PRODUCT STRENGTHS**

- Flooring and walls
- Can be diluted in water in any ratio
- Suitable for use with compact and porous materials
- Suitable for delicate marbles
- Ideal for internal environments

**AREAS OF USE**

**Use**  
To eliminate residues and streaks of Fugalite® Eco from ceramic surfaces.

**Substrates:**

- ceramic and homogeneous tiles
- glass mosaic, marble and natural stone

**Do not use**  
On surfaces that are not resistant to basic agents.

**INSTRUCTIONS FOR USE**

**Preparation of substrates**  
The coating materials must first be cleaned to remove any dust. Fugalite® Eco must be fully hardened.

**Preparation**  
Fuga-Soap Eco is a ready-to-use yellowish liquid, water-dilutable in any ratio depending on the type of dirt to be removed. Shake the bottle well before opening in order to redisperse the liquid evenly.

**Application**  
It is advisable to perform a preliminary test on tiles that are not to be laid, or in a concealed area. Apply Fuga-Soap Eco evenly to the surface to be cleaned and leave it until the dirt to be removed begins to visibly lift; this may take a few minutes or up to 10-30 minutes depending on the quantity, the elapsed time after laying (at least 24 hours) and the degree of absorption of the substrate. Scrape the surface mechanically with abrasive felt pads. Once cleaned, rinse well and dry carefully. The use of wet vacuum makes the operation easier and ensures the complete removal of residue. In the case of large surface areas, a mechanical buffer with an abrasive felt pad for the removing operation is recommended. Repeat for highly stubborn dirt.

**Cleaning**  
Residues of Fuga-Soap Eco can be cleaned from tools by rinsing them thoroughly with water.

## SPECIAL NOTES

Fuga-Soap Eco is a liquid detergent. Before using the product, it is advisable to hermetically seal all doors, windows, rubber seals, furniture, varnished/painted elements, bathtubs and shower trays made of synthetic materials such as methacrylate, PVC, etc..and any surface that could be attacked through direct contact with the detergent or with vapours.

## ABSTRACT

Remove residues and streaks of Fugalite® Eco, from ceramic tiles, porcelain tiles, glass mosaic, marble and natural stone with an eco-friendly, water-based detergent, Eco 3 GreenBuilding Rating, such as Fuga-Soap Eco by Kerakoll Spa. Apply evenly to the surface to be treated, remove dirt with mechanical means and rinse thoroughly, for an average coverage of 1 l = 10 – 20 m<sup>2</sup>.

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	yellowish liquid
Specific weight	≈ 1,01 kg/dm <sup>3</sup>
Shelf life	≈ 24 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Pack	bottles 1 l
Water dilution ratios	All ratios
Viscosity	≈ 211 mPa · s, rotor 2 RPM 50 Brookfield method
pH	≈ 12,5
Temperature range for application	from +5 °C to +35 °C
Waiting time before cleaning with water	≈ 10 – 30 min.
Coverage	≈ 10 – 20 m <sup>2</sup> /l

*Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate and of the materials laid.*

## WARNING

- **Product for professional use**
- abide by any standards and national regulations
- store and use at a temperature above +5 °C. Protect from frost
- Rinse thoroughly all surfaces treated
- Do not leave cans or bottles open, even during use
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Eco and Bio classifications refer to the GreenBuilding Rating Manual 2012. This information was last updated in October 2012 (ref. GBR Data Report - 11.12); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.

Kerakoll  
Quality  
System

ISO 9001  
CERTIFIED

**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)