

Slc® Eco Diluente Oil

Eco-friendly thinner for oil-based and oil-urethane varnishes and waxes, ideal for use in GreenBuilding. Single-component with no environmental hazard rating, safeguards the health of operators.

Slc® Eco Diluente Oil is a mixture of solvents developed for Slc® Eco Oil-Pur, Slc® Eco Oil-Deck HPX, and Slc® Eco Cera which guarantees increased fluidity and penetration. Specifically intended to remove residues and clean equipment.



GREENBUILDING RATING®

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

PRODUCT STRENGTHS

- High level of purity
- High solvent power mix that is highly compatible with oil and oil-urethane based products

AREAS OF USE

Use
Specifically intended for diluting:

- Slc® Eco Oil-Pur, Slc® Eco Oil-Deck Hpx, Slc® Eco Cera, Slc® Eco Silocera
- waxes and solvents
- pickling, removal of stains and residues on wood floors treated with wax

Interior wood floors in residential buildings.

Do not use
For the dilution of solvent and water based, base coat and top coat varnish, primer and waterproofing products, adhesives in general.

INSTRUCTIONS FOR USE

Preparation
The product is ready-to-use.

Application
For the dilution of Slc® Eco Oil-Pur, Slc® Eco Cera, and Slc® Eco Silocera add 5 – 10 % of Slc® Eco Diluente Oil according to need and the instructions on the product technical data sheets.
For the dilution of Slc® Eco Oil-Deck HPX add up to 50 % of Slc® Eco Diluente Oil according to need and the instructions on the product technical data sheets.
For pickling and the removal of stains and old layers of wax, and when necessary on untreated wood, rub the floor surface with a clean cloth soaked in Slc® Eco Diluente Oil.
For cleaning and removing remains of product from tools, clean with a cloth soaked in Slc® Eco Diluente Oil. If necessary, leave the tools to soak in Slc® Eco Diluente Oil, dry the tools with care before use.

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	Dark Brown liquid
Pack	oilers 5 l
Shelf life	≈ 12 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +35 °C
Boiling point	+146 °C
Flash point	+36 °C
Density at +20 °C	0,79 g/cm ³

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbcency level of the substrate.

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- respect the dilution ratios suggested in this data sheets and in the data sheet mentioned above
- respect the suggested dilution ratios and do not apply excessive amounts of product
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in October 2014 (ref. GBR Data Report - 11.14); please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com