

Slc® Eco Silomac

Eco-friendly cleaner to remove stains and residues of organic adhesives for hardwood floors, ideal for use in GreenBuilding. Single-component, safeguards the health of both operators and the environment.

Slc® Eco Silomac easily removes stains and residues of organic wood adhesives from the surface of pre-finished wood and plastic laminate floors without damaging them.



GREENBUILDING RATING®

				No environmental hazard rating	Non-toxic and non-hazardous

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

PRODUCT STRENGTHS

- Cleans thoroughly
- Does not damage varnishes normally used on pre-finished floors

AREAS OF USE

Use
Removal of stains and traces of adhesive from:

- pre-varnished wooden floors
- plastic laminate

Interior floors.

Do not use
On untreated and unvarnished wood floors, on wood floors coated with water-based varnishes.

INSTRUCTIONS FOR USE

Preparation
The product is ready-to-use.

Application
Using a soft, clean cloth dampened with Slc® Eco Silomac, pat the stains until they soften, then remove them without rubbing. Repeat the application if necessary.

SPECIAL NOTES

In the case of stubborn stains, leave the product to work for a few minutes.

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	Transparent liquid
Pack	1 l tins
Shelf life	≈ 6 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +30 °C

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.

WARNING

- Product for professional use

- abide by any standards and national regulations
- before use, check the resistance of the varnish or laminate to Slc® Eco Silomac by applying a little in a hidden area
- do not rub the glue when it has been softened using Slc® Eco Silomac, as the mineral fillers in the glue itself might damage the film of varnish
- never pour large amounts of Slc® Eco Silomac when cleaning wood floors
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in August 2014 (ref. GBR Data Report - 09.14); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com