







Slc® Eco Silopark

Eco-friendly soap to clean floors and surfaces, ideal for use in GreenBuilding. Concentrate, water-based, with low solvent content, safeguards the health of both operators and the environment.

Neutral-action Slc® Eco Silopark cleans varnished and pre-finished hardwood floors, as well as plastic laminate, PVC, rubber, linoleum, marble and ceramic floors perfectly without damaging the surface.



GREENBUILDING RATING®					
					
	✓	✓	✓	✓	✓
	Water-based formulation	Reduced solvent content 0,5 g/kg	No environmental hazard rating	Non-toxic and non-hazardous	
RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS					

PRODUCT STRENGTHS

- High-coverage concentrate
- Ready-to-use for the localized removal of stubborn dirt
- Cleans thoroughly, no need to rinse
- Highly biodegradable

AREAS OF USE

Use

Cleaning of:

- traditional and pre-finished varnished and oiled hardwood floors
- pre-varnished and oiled wooden floors
- varnished and oiled bamboo floors
- plastic laminate
- vinyl floors
- rubber
- linoleum
- marble, ceramic tiles

Interior floors.

Do not use

On untreated or unvarnished hardwood floors.

INSTRUCTIONS FOR USE

Preparation

The product is ready-to-use.

Dilute with lukewarm water in the ratio Slc® Eco Silopark : water = 1 measuring cap : 3 ℓ

Application

Soak a mop cloth and wring it out, then wipe the surfaces to be cleaned. Occasionally dip the cloth in the cleaning solution again, wring it out, and continue cleaning. No need to rinse.

SPECIAL NOTES

When cleaning small surfaces and/or stubborn stains, pour Slc® Eco Silopark directly onto a damp cloth and rub locally.

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	Transparent liquid
Pack	bottles 1 ℓ
Shelf life	≈ 12 months in the original packaging in dry environment
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +30 °C
Biodegradability	≥ 90%
Coverage using mop	≈ 1 measuring cap in 3 ℓ of water

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- while cleaning do not douse the surface to be cleaned with water and/or cleaning solution
- ventilate premises adequately to facilitate drying
- do not walk over or cross wet flooring until it has completely dried
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in August 2014 (ref. GBR Data Report - 09.14); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com