

# Slc® Eco Oil-Deck Care

**Eco-friendly soap-oil for maintaining wood flooring and products treated with Slc® Eco Oil-Deck HPX, ideal for use in GreenBuilding. Water-based concentrate, reduced solvent content, safeguards the health of both operators and the environment.**

Slc® Eco Oil-Deck Care thoroughly cleans and nourishes wood fibres in wood floors and structures in external applications treated with Slc® Eco Oil-Deck HPX.



**GREENBUILDING RATING®**

**Slc® Eco Oil-Deck Care**  
 - Category: Liquid organic products  
 - Class: Detergents, Protective products and Waxes for Hardwood floors  
 - Rating: Eco 4

	 Low Emission Indoor Air Quality	 Water Based	 SLV REDUCED Solvent < 80 g/kg	 Low Ecological Impact	 Health Care
		Water-based formulation	Reduced solvent content 2 g/kg	No environmental hazard rating	Non-toxic and non-hazardous

RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

**PRODUCT STRENGTHS**

- High-coverage concentrate
- Cleans thoroughly and nourishes fibres
- Highly biodegradable

**AREAS OF USE**

**Use**  
 Cleaning of surfaces treated with Slc® Eco Oil-Deck HPX

External wooden floors and elements.

**Do not use**  
 On untreated and unvarnished wood floors, on various coated wood floors and prefinished hardwood floors.

**INSTRUCTIONS FOR USE**

**Preparation**  
 Dilute with lukewarm water in the ratio Slc® Eco Oil-Deck Care : water = 1 part : 10 parts.

**Application**  
 Soak a mop or a cloth and wring it out, then wipe the surfaces to be cleaned. Occasionally dip the cloth in the cleaning solution again, wring it out, and continue cleaning. No need to rinse.

## SPECIAL NOTES

When cleaning small surfaces and/or stubborn stains, pour Slc® Eco Oil-Deck Care directly onto a damp cloth and rub locally.

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	Yellow-ivory cream
Pack	5 l cans
Shelf life	≈ 12 months in the original packaging in dry environment
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +30 °C
Biodegradability	≥ 90%
Coverage using mop	≈ 100 ml in 1 litro d'acqua

*Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.*

## WARNING

### - Product for professional use

- abide by any standards and national regulations
- while cleaning do not douse the surface to be cleaned with water and/or cleaning solution
- if necessary, ask for the safety data sheet
- do not walk over or cross wet flooring until it has completely dried
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in November 2013 (ref. GBR Data Report - 12.13); please note that additions and/or amendments may be made over time by KERAKOLL SpA; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.

Kerakoll  
Quality  
System

ISO 9001  
CERTIFIED

**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)