

# Slc® Eco Silocera

**Eco-friendly wax to maintain hardwood floors treated with Slc® Eco Cera, ideal for use in GreenBuilding. Single-component, safeguards the health of both operators and the environment.**

Slc® Eco Silocera makes it easy to maintain wood floors with a *wax finish* thanks to the mix of different hard waxes.



**GREENBUILDING RATING®**


RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS

**PRODUCT STRENGTHS**

- Easy to apply
- Can be polished with machine polisher
- Revitalizes and restores surface shine
- Forms a water-repellent protective layer

**AREAS OF USE**

**Use**  
Maintenance of wooden floors treated with Slc® Eco Cera or Slc® Eco Oil-Pur.

Interior floors

**Do not use**  
On unvarnished and untreated wood floors, on various coated wood floors and prefinished hardwood floors.

**INSTRUCTIONS FOR USE**

**Preparation of substrates**  
Carefully clean the wood floor with Slc® Eco Silopark (according to the instructions supplied on the technical data sheet). If necessary, remove any resistant stains, or old layers of wax with Slc® Eco Diluente Oil .

**Preparation**  
The product is ready-to-use. Shake the container before use.

**Application**  
Evenly apply a thin layer of Slc® Eco Silocera with a clean woollen or cotton cloth, or with a wax applicator. After it is completely dry, polish with a soft cloth or with a polishing machine.

**Cleaning**  
Clean the residues of Slc® Eco Silocera with Slc® Eco Diluente Oil when the product is fresh.

**SPECIAL NOTES**

To give an even effect, apply layers of uniform thickness and follow the recommended quantities  
Use Slc® Eco Silopark according to the instructions provided in the product technical data sheet to clean floors that have been treated with Slc® Eco Silocera  
For the maintenance of floors treated with Slc® Eco Silocera: repolish the surface with a cotton cloth with a polishing machine to renew the shine and to eliminate any marks and prints, apply Slc® Eco Silocera and polish to regenerate the surface protection layer.

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	White liquid
Pack	1 ℓ tins
Shelf life	≈ 12 months in the original packaging in dry environment
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	≥ +10 °C
Suitable for overlaying	≈ 1 hr
Coverage	≈ 10 – 20 ml/m <sup>2</sup> per coat

*Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbcency level of the substrate.*

## WARNING

- **Product for professional use**
- abide by any standards and national regulations
- adequately ventilate the area to facilitate drying
- do not walk over or cross wet flooring until it has completely dried
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2012. This information was last updated in September 2014 (ref. GBR Data Report - 10.14); please note that additions and/or amendments may be made over time by KERAKOLL SpA, for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)