

# Slc® Eco Siloleva

**Eco-friendly, wax-removing detergent for the deep cleaning of floors, ideal for use in GreenBuilding. Concentrate, water-based, safeguards the health of both operators and the environment.**

Slc® Eco Siloleva thoroughly cleans and removes residues of previous wax coatings from varnished and pre-finished hardwood floors, as well as plastic laminate, PVC, rubber and linoleum floors without damaging the surface.



GREENBUILDING RATING®					
		✓		✓	✓
		Water-based formulation		No environmental hazard rating	Non-toxic and non-hazardous
RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS					

PRODUCT STRENGTHS
<ul style="list-style-type: none"> <li>• Ideal when cleaning prior to the application of Slc® Eco Silolux or Slc® Eco Silowax</li> <li>• Specifically intended to remove old layers of Slc® Eco Silolux and Slc® Eco Silowax</li> </ul>

AREAS OF USE
<p><b>Use</b></p> <p>Deep cleaning and removal of layers of wax from:</p> <ul style="list-style-type: none"> <li>- floors in PVC, rubber, and linoleum</li> <li>- Varnished and pre-finished wood floors</li> <li>- Floors treated with Slc® Eco Silowax or Slc® Eco Silolux</li> </ul> <p><b>Do not use</b></p> <p>For removing layers of waxes and solvents, for cleaning varnished wood floors.</p>

INSTRUCTIONS FOR USE
<p><b>Preparation</b></p> <p>The product is ready-to-use.</p> <p>Dilute one part of Slc® Eco Siloleva with 5 – 10 parts of lukewarm water.</p> <p><b>Application</b></p> <p>Apply the solution on the floor and leave it to work for 5 minutes. Rub with a cloth and large brush or wipe with a floor cleaning machine equipped with a stiff brush and collect the dirt removed. Repeatedly rinse with clean water to remove all the residues of dirt and waxes.</p>

SPECIAL NOTES
<p>If thick or very old layers have to be removed, then a greater concentration and a longer waiting time are recommended.</p> <p>Do not leave Slc® Eco Siloleva solution to dry on the floor: if necessary wet it again with a little lukewarm water to avoid stains forming.</p> <p>Check colour resistance before using it to clean linoleum floors: if necessary apply a more diluted solution and leave it to work more briefly.</p> <p>Pay particular attention when washing varnished wood floors with water-based varnishes: do not use Slc® Eco Siloleva, but only neutral detergents.</p> <p>Composition (CEE 89/542 Recommendations) non-ionic surfactants: 10 – 15%, non-chlorinated organic solvents: 15 – 20%; phosphates: less than 2% (P &lt; 0.5).</p> <p>Biodegradability: above 90% (Art. 7 Law 26.04.1983 Nr. 136).</p>

## TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	Transparent liquid
Pack	bottles 1 l
Shelf life	≈ 12 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
Temperature range for application	from +10 °C to +30 °C
Drying	≈ 1 hr
Coverage using cloth	≈ 20 – 30 ml/m <sup>2</sup>

*Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.*

## WARNING

### - Product for professional use

- abide by any standards and national regulations
- do not pour large amounts of water and/or detergent solution over the surface to be cleaned when using
- ventilate premises adequately to facilitate drying
- do not walk or pass by on wet or not yet completely dry floors
- follow all applicable safety regulations and guidelines when using the product
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - [globalservice@kerakoll.com](mailto:globalservice@kerakoll.com)

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in October 2014 (ref. GBR Data Report - 11.14); please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see [www.kerakoll.com](http://www.kerakoll.com). KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



**KERAKOLL**  
The GreenBuilding Company

KERAKOLL S.p.a.  
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy  
Tel +39 0536 816 511 - Fax +39 0536 816 581  
[info@kerakoll.com](mailto:info@kerakoll.com) - [www.kerakoll.com](http://www.kerakoll.com)