

Slc® Eco Proman

Eco-friendly, breathable barrier cream to protect the hands from the most common aggressive agents, ideal for use in GreenBuilding. Single-component, solvent-free, safeguards the health of both operators and the environment.



Slc® Eco Proman creates a breathable barrier to protect the hands from oil, grease, varnishes, resins, adhesives, tar, petrol, silicon, solvents and synthetic products in general. Can be easily cleaned at the end of application with soap and water.

GREENBUILDING RATING®					
	✓	✓	✓	✓	✓
	Water-based formulation	Solvent-free	No environmental hazard rating	Non-toxic and non-hazardous	
RATING SYSTEM ACCREDITED BY CERTIFICATION BODY SGS					

PRODUCT STRENGTHS
<ul style="list-style-type: none"> • Dermatologically-tested • Forms a protective, breathable barrier • Easy to remove

AREAS OF USE
<p>Use Protection of the hands from dirt and aggressive substances such as solvents, varnishes, glues, resins, adhesives, tar, petrol, silicon, oils, greases, synthetic products.</p>

INSTRUCTIONS FOR USE
<p>Application Before starting work, evenly spread a sufficient quantity of cream on the hands without neglecting the finger nails and the areas around them. After a few minutes, the product will dry forming an thin invisible barrier on the skin that suitably protects from the substances indicated above. A greater protection can be obtained with a double application of the product. Periodically renew the application for jobs of a long duration.</p> <p>Cleaning To remove any dirt remaining on the hands and to remove the film of barrier cream at the end of work only needs a wash with lukewarm water scrubbing forcibly with soap.</p>

00249Slc® Eco Proman Code: Slc 193 2014/01 EN

SPECIAL NOTES

Slc® Eco Proman protective film is not sticky and does not leave prints
Does not make the hands sweat
It is a dermatologically tested product

TECHNICAL DATA COMPLIANT WITH KERAKOLL QUALITY STANDARD

Appearance	white coloured paste
Pack	500 ml tin
Shelf life	≈ 12 months in the original packaging
Warning	Protect from frost, avoid direct exposure to sunlight and sources of heat
pH	neutral (7)
Temperature range for application	from +10 °C to +30 °C
Drying	≈ 5 mins
Coverage	≈ 100 applications with one pot

Values taken at +23 °C, 50% R.H. and no ventilation. Data may vary depending on specific conditions at the building site, i.e. temperature, ventilation and absorbency level of the substrate.

WARNING

- **Product for professional use**
- abide by any standards and national regulations
- if necessary, ask for the safety data sheet
- for any other issues, contact the Kerakoll Worldwide Global Service +39 0536 811 516 - globalservice@kerakoll.com

The Eco and Bio classifications refer to the GreenBuilding Rating® Manual 2013. This information was last updated in October 2014 (ref. GBR Data Report - 11.14); please note that additions and/or amendments to this information may be made over time by KERAKOLL Spa; for the latest version, see www.kerakoll.com. KERAKOLL SpA shall therefore be liable for the validity, accuracy and updating of information provided only when taken directly from its institutional website. The technical data sheet given here is based on our technical and practical knowledge. As it is not possible for us to directly check the conditions in your building yards and the execution of the work, this information represents general indications that do not bind Kerakoll in any way. Therefore, it is advisable to perform a preliminary test to verify the suitability of the product for your purposes.



KERAKOLL
The GreenBuilding Company

KERAKOLL S.p.a.
Via dell'Artigianato, 9 - 41049 Sassuolo (MO) Italy
Tel +39 0536 816 511 - Fax +39 0536 816 581
info@kerakoll.com - www.kerakoll.com